





Avenue de la liberté 14 janvier Imm. ITKANE, 3ème étage, B11.CP. 3027-sfax, Tunisie

Tel: +216 74 415 055 Site web: www.asmpos.com Fax: +216 74 415 044 E-mail: contact@asm.com.tn





Rugged and Versatile

The 9200 series mobile computer is precisely constructed with durability, functionality and flexibility. Being pocket-sized, it's extremely rugged with IP65 standards and 1.5 m drop onto concrete, which ensures efficiency in harsh conditions. Operating on a 3300 mAh battery, 9200 series can utilize its versatile reader options such as linear imager, laser, 2D imager, and RFID throughout the day. It also provides flexible wireless communications in 3.5G HSDPA with GPS/ AGPS, Bluetooth® communication and IEEE 802.11 a/b/g/n for extended indoor and outdoor communication needs. Having all these functions in your hands paired with an ergonomic design of a 3 megapixel camera for easy documentation and enhanced keypad for easy data entry truly makes 9200 series mobile device a dependable work of wonder.



Ergonomic Designs Suitable for In-premise Environments

CipherLab 9200 series is compactly built with excellent ruggedness for smooth operating in any in-premise environments. It is capable of enduring exposure to dust, dirt and splashing water with its IP65 rating. Built with a 1.5 m drop to concrete resistance, the 9200 series easily avoids accidental drop problems. Its ruggedness is coupled with a compact and lightweight design to provide comfortable one-hand usage.



The flexible wireless features of the 9200 series will keep your connection strong and solid. The 3.5G HSDPA with GPS/ AGPS allows quality data communication along with navigational tracking information to fully expand worker productivity. With IEEE 802.11 a/b/g/n technology and Bluetooth® communication, you can easily deliver real-time data transmission to access critical information, update backend systems and have full compatibility with Bluetooth® peripherals. IEEE 802.11 a/b/g/n extends your applications to higher level functions for additional needs.







Long Lasting Data Capture Capabilities with Versatility

The 9200 series operates on a 3300 mAh battery which minimizes the need to change batteries and allows easy data capturing for extended time. With long lasting power, it also supports versatile reader options in linear imager, laser, 2D imager, and RFID to effectively assist you with different scanning needs. Having long lasting power along with these capabilities can absolutely provide an efficient solution to wider data collecting demands.



Efficient and Comfortable Operation in the Field

With the built-in 3 megapixel camera, workers are equipped to capture images for visual verification with home office or customers – improving workforce productivity and eliminate potential mistakes which may lead to customer service dissatisfaction. All of this can be done without the additional costs of separate digital camera. The 9200 series also includes enhanced numeric keypads which makes operation easy for workers even if they are wearing gloves. It additionally includes a 2.8" QVGA touch screen display with transflective TFT LCD so you can easily operate and read under sunlight or dim warehouses.



More Support for Data, Device, and Performance Management

Software for Advanced Applications

KALIPSO Mobile Application Generator for Easy and Quick Customization

SYSDEVI) KALIPSO

A third party application generator software tool designed for Windows-based mobile computers, KALIPSO Mobile Application Generator helps users customize application needs effortlessly. With free demo programs like inventory check, order entry, and proof-of delivery, users could start the applications right away.



App-Lock for Optimized Management over Work Productivity and Performance

App-Lock is designed to improve work productivity and performance management with full control over all executable files saved in the 9200 series. Limited access can be set to essential device settings and pre-approved applications to keep workers focused on the tasks at hand. Setup files can also be copied and deployed to other devices in the field remotely to increase the efficiency of device management.

SOTI MobiControl for Improved Device Management in the Field



Improve mobile workforce performance and efficiency with a complete software solution. SOTI MobiControl for CipherLab 9200 series enables access to a robust set of features that support remote management without requiring your mobile

MIRROR Browser and Emulator for Extended Data Capture Support

The MIRROR Browser empowers the 9200 series to integrate seamlessly into web-based environments, turning it into an accurate, effective and user-friendly data capture tool for any web-based task.







	Operating System	Windows Embedded Handheld 6.5
Performance	CPU	Qualcomm™ 7225-1 528MHz
	Memory	512MB Flash / 256MB DDR SDRAM
	Expansion	micro SD slot with SDHC support (up to 32 GB)
	Operating power	Rechargeable 3.7V 3300 mAh Li-ion battery
	Working hours¹	12 hours
	Alert	Dual-color LEDs, vibrator, speaker
Wireless communication	Interface supported	16 Pin I / O connector, USB 2.0, RS232
	WWAN ²	GSM / GPRS / EDGE / WCDMA / HSDPA GSM band: 850 / 900 / 1800 / 1900, UMTS band: 850 / 2100
	WLAN	IEEE 802.11 b/g / IEEE 802.11 a/b/g/n (Cisco® CCX v4 certified)
	WLAN security	WEP, WPA (TKIP, AES, PSK), WPA2 (TKIP, AES, PSK)
	WPAN	Bluetooth® Class II, V2.1 with Enhanced Data Rate (EDR)
	Bluetooth® profile	GAP, SDP, GOEP, SPP, OPP, DUN, A2DP, PAN, HID, HSP, HFP, AOB, AVRCP
	GPS	GPS/ AGPS/ XTRA
Data capture	Barcode scanning	1D Laser/ 1D CCD/ 2D imager
	RFID (read / write)	HF RFID 13.56 MHz frequency Support Tags: ISO14443A (Mifare), ISO14443B, ISO15693
Physical characteristics	Camera	3 megapixels CMOS with LED flash and autofocus
	Display	2.8" QVGA transflective TFT color LCD with LED backlight
	Keypad	23-key Numeric keypad with LED backlight
	Size (L x M x H)	175 x 60 x 34 mm
User environment	Weight (laser including battery)	310 g
	Operating temperature ³	-20°C to 50°C / -4°F to 122°F
	Storage temperature	-30°C to 70°C / -22°F to 158°F (w/o battery)
	Humidity (non-condensed)	Operating: 10% ~ 90% Storage: 5% ~ 90%
	Impact resistance	1.5 m multiple drops onto concrete, 5 drops on each side / IP65 / 1000 tumbles at 0.5 m
	Electrostatic discharge	± 15 kV air discharge, ± 8 kV contact discharge
	EMC regulation	RCM, FCC, CE, NCC, SRRC, CCC, MII, RCM, TELEC, JATE
Development support		Cipherlab C++ / .NET,SDK to support Microsoft® Visual studio 2005, Microsoft® Visual Studio 2008
Application software		App-Lock, Camera Application, Mobile Network Wizard, Mobile Ghost, Button Assignment, GPS Manager, Reader Configuration, Signature Capture, TimeSync,Terminal Emulation, CipherLab SmartShell, CipherLab MIRROR Browser, Kalipso Mobile Application Generator, Naurtech CETerm, SOTI MobiControl, Wavelink Avalanche and Emulators
Warranty		1 year

1. Minimum 12 hours under WLAN and laser scanning per 20 seconds, LCD 50% backlight and speaker on (volume is default) at 25°C, RFID off / Bluestooth® off / IEEE 802.11 b/g on. The test is based on one broadcasting packet per second.

2. The mobile computer has received general telecommunication certification for data communication. Please check with your local carrier for the optimum operating efficiency.

3. Varied by product configuration.









4-slot battery charger



Snap-on cable (USB / RS232)



Snap-on car charger



Avenue de la liberté 14 janvier Imm. ITKANE, 3ème étage, B11.CP. 3027-sfax, Tunisie

Site web: www.asmpos.com Tel: +216 74 415 055 Fax: +216 74 415 044 E-mail: contact@asm.com.tn

